RZR PRO XP Premium Indy Red





Key Specifications

64" 181 14.5" WIDTH HP CLEARANCE

Engine & Drivetrain

Cooling	Liquid
Cylinders Displacement	925cc
Drive System Type	Isolated Xtreme Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	Turbo H.O.; 4-Stroke DOHC Twin Cylinder Turbocharged
Fuel System/Battery	Electronic Fuel Injection
Horsepower	181 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

Dimensions

Bed Box Dimensions (L x W x H)	26 x 17.7 x 11.5 in (66 x 45 x 29.2 cm)
Box Capacity	300 lb (136.1 kg)
Dry Weight	1,749 lbs (795.1 kg)
Fuel Capacity	12 gal (45.4 L)
Ground Clearance	14.5 in (36.8 cm)
Overall Vehicle Size (L x W x H)	126.1 x 64 x 71.7 in (320 x 163 x 182 cm)
Payload Capacity	740 lb (336 kg)
Wheelbase	96 in (244 cm)

Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers
Parking Brake	Park In-Transmission

Additional Specifications

Cargo System	Lock & Ride
Doors	Vented 1/2 Doors
Electronic Suspension Control System	N/A
Hitch Towing Rating	N/A
Hitch Type	Not Equipped
Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet
Lighting	Signature White LED, Low/High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting
Other Standard Features	900W stator, Polaris Pulse system, DC Charging
Seat Type	Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat slider with tilt adjustability) and Retractable Click-6 Harnesses

Tires / Wheels

Electronic Power Steering	Standard with improved telescoping Steering Wheel
Front Tires	30 x 10-14 MAXXIS Carnivore; Wheel Size 14x6
Rear Tires	30 x 10-14 MAXXIS Carnivore; Wheel Size 14x7
Wheels	Cast Aluminum

Suspension

Front Shocks	2 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
Front Suspension	High-Clearance Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel, 17 in (43.2 cm) Wheel Travel
Rear Shocks	2.5 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
Rear Suspension	Trailing Arm with Stabilizer Bar and 22" (55.9 cm) Usable Travel, 20" (50.8 cm) Wheel Travel