

RZR PRO XP Ultimate Matte Titanium Metallic



Key Specifications

181

HP

64"

WIDTH

14.5"

CLEARANCE

Engine & Drivetrain

Cooling	Liquid
Cylinders Displacement	925cc
Drive System Type	Isolated Xtreme Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke DOHC Twin Cylinder Turbocharged
Fuel System/Battery	Electronic Fuel Injection
Horsepower	181 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

Dimensions

Bed Box Dimensions (L x W x H)	26 x 17.7 x 11.5 in (66 x 45 x 29.2 cm)
Box Capacity	300 lb (136.1 kg)
Estimated Dry Weight	1,795 lb (814 kg)
Fuel Capacity	12 gal (45.4 L)
Ground Clearance	14.5 in (36.8 cm)
Hitch Towing Rating	N/A
Overall Vehicle Size (L x W x H)	126.1 x 64 x 71.7 in (320 x 163 x 182 cm)
Payload Capacity	740 lb (336 kg)
Wheelbase	96 in (244 cm)

Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers
-------------------	---

Parking Brake	Park In-Transmission
----------------------	----------------------

Additional Specifications

Cargo System	Lock & Ride
Doors	Vented 1/2 Doors
Electronic Power Steering	High Assist Electronic Power Steering with Quick Turn Rack; Race inspired Steering Wheel with Tilt and Telescoping adjustment; Dynamix and Ride Command Push Button Controls
Hitch Type	Not Equipped
Instrumentation	RIDE COMMAND® 7" Glove-Touch Display: DYNAMIX 2.0 Visualizer, Digital Instrumentation, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets, Rockford Fosgate Premium Audio (Including 2 Tweeters, 2 Front Speakers, and External 400W Amp) Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet
Lighting	Signature White LED, Low/High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting
Other Standard Features	High Output 900w charging system with sealed electrical
Seat Type	Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat slider with tilt adjustability) and Retractable Click-6 Harnesses

Tires / Wheels

Front Tires	30 x 10-14 MAXXIS Carnivore (8-Ply); Wheel Size 14x6
Rear Tires	30 x 10-14 MAXXIS Carnivore (8-Ply); Wheel Size 14x7
Wheels	Cast Aluminum

Suspension

Electronic Suspension Control System	DYNAMIX 2.0 Active Suspension System
Front Shocks	FOX 2.5 Podium Live Valve with Bottom-Out Control (Electronically Controlled Damping)
Front Suspension	High-Clearance Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 17 in (43.2 cm) Wheel Travel
Rear Shocks	FOX 2.5 Podium Live Valve with Bottom-Out Control (Electronically Controlled Damping)
Rear Suspension	Trailing Arm & High-Clearance Radius Rods with Stabilizer Bar and 22 in (55.9 cm) Usable Travel*, 20 in (50.8 cm) Wheel Travel

